

# EVERPRIME BLEED BLOCK SS



## Water Resistant Acrylic Base Coat for Smooth Asphalt Surfaces

For Professional Use Only

### DESCRIPTION

- A high quality, plasticizer free, single component, water-based, 100% acrylic elastomeric coating.
- Designed to provide maximum adhesion and bleed-through resistance over smooth asphalt even in the presence of water.
- Designed to tolerate some standing water when reinforced with fabric.
- May be used over smooth or granulated substrates.
- Adheres to most Aluminized coatings (Adhesion should be verified prior to application)
- Formulated to act as a barrier to block discoloration.
- Has the unique ability to “breath”, providing a completely watertight membrane while allowing trapped moisture to escape.

### RECOMMENDED USES

Everprime Bleed Block SS Base is designed as a base coat for application over smooth surface asphalt such as built up and modified bitumen substrates. Everprime Bleed Block SS may be used in low areas and waterways when used in combination with reinforcing fabric. With a suitable top coat, it is an exceptional protective system for asphaltic membranes. Check with your Everest representative for top coat recommendations.

Property	Test Method	Result
Tensile Strength	ASTM D-2370	100 psi ±25
Elongation:	ASTM D-370	980% ± 25
Perms	ASTM D-1653	3
Solids Content by Weight	ASTM D-370	65% ± 2
Solids Content by Volume	ASTM D-1644	50% ± 2
Density	ASTM D-370	11.4 lbs gal
VOC	Method 24	<50 g/liter
Flash Point	ASTM D-1310	>212 ° F
Temperature Limit		0° F to 185° F
Low Temp Flexibility	ASTM D-522	Passes 180° F Flex over 1/8 Mandrel @ =30° F
Cure Time		24 hours depending on Temp. & Humidity
Dry Time		5 Hours at 75°F @ 50% m

### COLORS

Ivory – Satin Flat

### SURFACE PREPARATION

**General:** Surfaces to be coated should be dry, free of dust, dirt, oil, loose granules, peeling coating or other foreign matter.

### PACKAGING/SHIPPING INFORMATION

#### CONTAINER SIZE

55 Gallon drum (208.2 liters)

5 Gallon pail (18.9 liters)

#### SHIPPING CLASS

Class 55

Class 55

**EVEREST SYSTEMS LLC • 1926 Rankin Rd. #110 • Houston, TX 77073**

**www.EVERESTSYSTEMSCO.com • Phone 800-575-8966**

# EVERPRIME BLEED BLOCK SS



## Water Resistant Acrylic Base Coat for Smooth Asphalt Surfaces

### APPLICATION

This product may be brushed, rolled or sprayed on a clean, dry surface. In waterways or low areas material should be applied as follows:

- Apply Everprime Bleed Block SS Base at a rate of 1 gallon/sq.
- Immediately embed a layer of Evercoat 272 fabric in wet coating.
- Immediately apply a further application of Everprime SS Base at a rate of 1 gallon/sq.
- Allow to cure for at least 24 hours.

For details see Equipment Recommendations at the end of this sheet. It is critical that this be allowed to cure for a MINIMUM of 24 hours and even longer in cool or high humidity environments.

**Note: Blistering will occur if top coat is applied over base coat that is not completely dry** If any contamination of a thoroughly cured surface occurs, it must be washed with a chemical cleaner before applying subsequent coats. Hand application can be done with squeegee and roller.

### ENVIRONMENTAL CONDITIONS

Product should not be applied when the ambient temperature is below 32° F or the temperature will fall to within 5 degrees of the dew point within 6 hours after application. Do not apply in late afternoon if high humidity exists, it may cause high moisture condensation on the surface overnight.

### PONDED WATER

- Everest Systems warranties do not cover damage due to ponding water.
- The National Roofing Contractors Association considers ponding water on any roof unacceptable. (See the NRCA Roofing and Waterproofing Manual).

### LIMITATIONS

Surface must be clean and dry. Everprime Bleed Block SS Base is water based and requires evaporation to cure. Material must cure for at least 24 hours. Low temperature and high humidity will slow the cure process. In these situations, even longer cure times will be necessary. **Note: Blistering will occur if top coat is applied over base coat that is not completely dry** Do not apply Everprime Bleed Block SS Base if there is any moisture on the substrate or risk of precipitation. If applied where there is a risk of vapor drive, such as cold storage and refrigerated tank application there must be a suitable vapor barrier. Everprime SS Bleed Block Base is not intended as a thermal Barrier.

### SAFE PRACTICES

This product is designed for professional installation. Before working with this product, you must read and become familiar with the available information on its risks, proper use and handling. Information sources include but are not limited to SDS and product labels. More resources are available at [polyurethane.org](http://polyurethane.org), [sprayfoam.org](http://sprayfoam.org), [everestsystemsco.com](http://everestsystemsco.com) or by contacting Everest Systems directly.

### EQUIPMENT

Minimum Requirements:

#### Brush

- Synthetic Filament

#### Roller

- 1 ¼ nap roller

#### Spray

- Standard Contractor gun-no filters
  - Pressure 3000 psi at 2.5-3.0 gal/min
  - Tip .017-.029 reversible, self-cleaning with 40-50° fan angle
  - 12-inch wand extension recommended
- 3/8 "line for rated pressure

To the best of our knowledge all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. Used must contact Everest systems Company to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Everest Systems Products. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY EVEREST SYSTEMS EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

**EVEREST SYSTEMS LLC • 1926 Rankin Rd. #110 • Houston, TX 77073**

**[www.EVERESTSYSTEMSCO.com](http://www.EVERESTSYSTEMSCO.com) • Phone 800-575-8966**